Application No. 10/813,217 (60000500-1010) Amendment and Response dated **August 15, 2006** Reply to Office Action of June 5, 2006

IN THE CLAIMS:

01:22pm

1. (currently amended) An inert gas generating system for generating inert gas on a vehicle having a fuel tank and a fuel tank vent, said system comprising:

an inlet for receiving a flow of gas having a nitrogen component and an oxygen component from a gas source;

a heat exchanger downstream from the inlet and in fluid communication with the inlet for cooling gas received from the inlet; and

a gas separation module downstream from the heat exchanger and in fluid communication with the heat exchanger for separating gas received from the heat exchanger into a nitrogen-enriched gas flow and an oxygen-enriched gas flow, said; and

valving operatively connected to the gas separation module being adapted to deliver selectively delivering nitrogen-enriched gas from the nitrogen-enriched gas flow to the fuel tank without delivering the nitrogen-enriched gas through the fuel tank vent, said gas separation module being adapted to deliver and selectively delivering nitrogen-enriched gas from the nitrogen-enriched gas flow to the fuel tank vent.

- 2. (currently amended) A system in accordance with claim 1 further comprising wherein the valving comprises a flow valve operatively connected downstream from the gas separation module to control a flow rate of the nitrogeneniched gas flow received from the gas separation module.
- 3. (currently amended) A system in accordance with claim 1 in combination with wherein the valving comprises a fuel tank valve operatively connected between the gas separation module and the fuel tank to control a flow rate of nitrogeneniched gas into the fuel tank.
- 4. (currently amended) A system in accordance with claim 1 in combination with wherein the valving comprises a fuel tank vent valve operatively connected between the gas separation module and the fuel tank vent to control a flow rate of nitrogen-enriched gas into the fuel tank vent.

01:22pm

Application No. 10/813,217 (60000500-1010) Amendment and Response dated **August 15, 2006** Reply to Office Action of June 5, 2006

- 5. (Original) A system in accordance with claim 1 further comprising a flow sensor operatively connected downstream from the gas separation module to measure at least one of a flow rate and a pressure of the nitrogen-enriched gas flow downstream from the gas separation module.
- 6. (Original) A system in accordance with claim 1 further comprising an oxygen sensor operatively connected downstream from the gas separation module to measure an oxygen content of the nitrogen-enriched gas flow downstream from the gas separation module.
- 7. (Original) A system in accordance with claim 1 further comprising a compressor operatively connected between the inlet and the heat exchanger to increase a pressure of the gas received by the heat exchanger.
- 8. (Original) A system in accordance with claim 7 wherein operation of the compressor is driven by gas received from the inlet.
 - 9. (Original) A system in accordance with claim 7 further comprising:
- a pressure sensor operatively connected downstream from the compressor to measure a pressure of gas downstream from the compressor; and
- a compressor regulator valve operatively connected to the compressor and the pressure sensor for controlling operation of the compressor based on the pressure of the gas downstream from the compressor.
- 10. (Original) A system in accordance with claim 9 further comprising a processor operatively connected between the pressure sensor and the compressor regulator valve for controlling operation of the compressor regulator valve based on the pressure of the gas downstream from the compressor.

314 259 5959

Application No. 10/813,217 (60000500-1010) Amendment and Response dated **August 15, 2006** Reply to Office Action of June 5, 2006

- 11. (Original) A system in accordance with claim 7 further comprising a compressor bypass check valve operatively connected between the inlet and the heat exchanger to allow gas to bypass the compressor.
- 12. (Original) A system in accordance with claim 1 further comprising: a temperature sensor operatively connected downstream from the heat exchanger to measure a temperature of gas downstream from the heat exchanger; and a heat exchanger bypass valve operatively connected between the inlet and the gas separation module to allow gas to bypass the heat exchanger, said heat exchanger bypass valve operatively connected to the temperature sensor for controlling the temperature of the gas received by the gas separation module based on the temperature of the gas downstream from the heat exchanger.
- 13. (Original) A system in accordance with claim 12 further comprising a processor operatively connected between the temperature sensor and the heat exchanger bypass valve for controlling operation of the heat exchanger bypass valve based on the temperature of the gas downstream from the heat exchanger.
- 14. (Original) A system in accordance with claim 1 further comprising a ground connection port operatively connected between the heat exchanger and the gas separation module for introducing air to the gas separation module from a preconditioned air source external to the vehicle.
- 15. (Original) A system in accordance with claim 1 further comprising a filter operatively connected between the heat exchanger and the gas separation module to filter at least one of entrained moisture and particulate contaminants from gas flowing between the heat exchanger and the gas separation module.
- 16. (Original) A system in accordance with claim 1 wherein the gas separation module comprises a permeable membrane gas separation module.

Application No. 10/813,217 (60000500-1010) Amendment and Response dated **August 15, 2006** Reply to Office Action of June 5, 2006

- 17. (currently amended) A system in accordance with claim 1 further comprising a ground connection port operatively connected downstream from the gas separation module for introducing nitrogen-enriched gas from a nitrogen-enriched gas source external to the aircraft vehicle to at least one of the fuel tank and the fuel tank vent, and to allow withdrawal of nitrogen-enriched gas from the nitrogen-enriched gas flow generated by the gas separation module.
 - 18. (currently amended) An aircraft comprising:

an airframe:

a fuel tank mounted on the airframe;

a fuel tank vent operatively connected to the fuel tank; and

an inert gas generating system for generating inert gas on-board the aircraft, said inert gas generating system comprising:

an inlet for receiving a flow of air from an air source;

a heat exchanger downstream from the inlet and in fluid communication with the inlet for cooling air received from the inlet; and

a gas separation module downstream from the heat exchanger and in fluid communication with the heat exchanger for separating air received from the heat exchanger into a nitrogen-enriched gas flow and an oxygen-enriched gas flow, said; and

valving operatively connected to the gas separation module being adapted to deliver selectively delivering nitrogen-enriched gas from the nitrogen-enriched gas flow to the fuel tank without delivering the nitrogen-enriched gas through the fuel tank vent, said-gas separation module being adapted to deliver and selectively delivering nitrogen-enriched gas from the nitrogen-enriched gas flow to the fuel tank vent.

19. (Original) An aircraft in accordance with claim 18 wherein said inert gas generating system further comprises a ground connection port operatively connected between the heat exchanger and the gas separation module for introducing

Application No. 10/813,217 (60000500-1010) Amendment and Response dated August 15, 2006 Reply to Office Action of June 5, 2006

gas to the gas separation module from a pre-conditioned gas source external to the aircraft.

- 20. (Original) An alrcraft in accordance with claim 18 wherein said inert gas generating system further comprises a ground connection port operatively connected downstream from the gas separation module for introducing nitrogenenriched gas from a nitrogen-enriched gas source external to the aircraft to at least one of the fuel tank and the fuel tank vent, and to allow withdrawal of nitrogen-enriched gas from the nitrogen-enriched gas flow generated by the gas separation module.
- An aircraft in accordance with claim 18 further 21. (Original) comprising a gas turbine engine for propelling the aircraft and an environmental control system for conditioning bleed air from the engine, wherein the air source includes at least one of the gas turbine engine and the environmental control system.

22-45. (canceled)

46. (Original) An inert gas generating system for generating inert gas on a vehicle having a fuel tank, said system comprising:

an inlet for receiving a flow of gas having a nitrogen component and an oxygen component from a gas source;

a heat exchanger downstream from the inlet and in fluid communication with the inlet for cooling gas received from the inlet; and

a gas separation module downstream from the heat exchanger and in fluid communication with the heat exchanger for separating gas received from the heat exchanger into a nitrogen-enriched gas flow and an oxygen-enriched gas flow, said gas separation module being adapted to generate a flow rate of the nitrogen-enriched gas flow of about 40 pounds per minute with an oxygen content less than or equal to about 9.8 percent by volume.